

LISBON LUXOR – Interior / Exterior Paint Primer



DESCRIPTION

Lisbon Luxor Paint Primer Is A High Performance Cement Primer, Designed For Interior And Exterior Purposes. It Is Based On Alkali Resistant Acrylic Emulsion.

AREAS OF APPLICATION:

- Interior / Exterior Areas
- Concrete
- Cement Plaster
- Cement Based Wall Putty
- Gypsum Based Wall Putty
- Acrylic Based Wall Putty
- Cement Backer Boards*
- Gypsum Wall Boards* With Paper Face
- Calcium Silicate Boards*

ADVANTAGES:

- Non-toxic
- Non-corrosive
- Bio-degradable
- Low Voc
- Weather Resistant

APPLICATION:

Surface Preparation:

Clean Substrate To Eliminate Dust, Dirt, Oil, Grease, Paint Or Any Contaminants Which May Affect Bonding. Do Not Use Chemicals To Clean Substrate. Remove Any Loose Particles By Vacuuming And Damp Sponging.

MIXING:

Mixing Dilute With Clean Water According To The Ratios Given In The Lisbon Luxor – Exterior, Water Based Cement Primer Mixing Guide Table. Water Amounts Should Be Carefully Measured To Ensure Proper Mix Ratio. Make Sure The Water Used Is Of Potable Quality To Get Best Results. Blend By Hand Or Using A Mixing Paddle.

PACKING:

Lisbon Luxor Paint Primer Is Available In 1, 4, 10 & 20 Litres Packs.

COVERAGE:

80 To 100 Sq.foot Per Liter Depending Upon The Porosity Of The Substrate.

Coverage May Vary Depending On Substrate, Ambient Temperature, Dilution And Application Method

APPLICATION:

Lisbon Luxor - Exterior, Water Based Cement Primer Can Be Sprayed, Roller, Brush Or Broom Applied To Prepared Surfaces. Avoid Puddling And Allow Becoming Dry- To- Touch (3–5 Hours After Application With Good Ventilation). For Best Results, And While The Primer Is Still Fresh, It Should Be Lightly Brushed To Ensure A Complete, Uniform Film Has Been Applied. Allow The Primed Surface To Completely Dry Before The Application Of Paint Or Putty Materials. Protect Areas From Direct Sunlight. Keep Primed Surface Clean. Maintain Adequate Ventilation During And After Application Of Primer To Help Ensure Quicker Drying.

CLEANING:

All Tools And Equipment Should Be Cleaned Immediately After Use, With Water.

TECHNICAL DATA:

Appearance:	White Liquid
Weight per liter in Kg. :	1.4 + 0.05
Ph:	9.0 + 1.0

STORAGE:

After Usage, Close The Container Well Sealed To Avoid Contamination And Damages. Store In Original Sealed Container Only. Store And Use Between Temperature 40 C And 400 C.

CAUTIONS:

LISBON LUXOR – Exterior, Water Based Cement Primer Is Water Based And Is Nonhazardous Under Normal Conditions Of Use.

In Case Of Skin Contact, Wash Immediately With Water. Wear Gloves And Protective Goggles.

When Spraying The Product, Avoid Breathing The Fine Mist.

Contact Your Local Lisbon Luxor Technical Sales Representative In Case Of Any Questions. Keep Out Of Reach Of Children.