

LISBON ACRYLIC BOND DISTEMPER



DESCRIPTION

LISBON ACRYLIC BOND DISTEMPER

is A Water Based, Interior Wall Paint. It Is The Best Quality Acrylic Distemper Which Gives The Walls A Delightful, Attractive, Matt Finish That Lasts For Ages. Humid Climatic Conditions.

FINISH

LISBON ACRYLIC BOND DISTEMPER

Gives Unmatched Durability And A Smooth Finish That Has No Equal In The Distemper Category

ACRYLIC CO-POLYMER

Lisbon Satin Gloss Emulsion Lasts Longer Than Cement Paint And Hence Proves More Economical In The Long Run. It Also Does Not Require Curing And Therefore Saves Time, Effort And Money During Application.

COLOUR

It is available in white & Violet.

COVERAGE

On smooth primed masonry surface

1 COAT 170 - 200 sq.ft/kg**

2 COATS 90 - 110 sq.ft/kg**

Conditions.

AVAILABLE PACKS

1, 2, 5, 10 & 20 Kg

PRE PAINTING STEPS PLASTER

New Masonary Surfaces Must Be Allowed To Cure Completely. It Is Recommended To Allow 25-30 Days As The Curing Time For New Masonary Surfaces.

CLEANING

Surface Should Be Free From Any Loose Paint, Dust Or Grease. Growths Of Fungus, Algae Or Moss Should Be Removed By Wire Brushing And Water.

FILLING FOR CRACKS

For filling cracks upto 3mm use suitable Crack Seal.

FILLING FOR HOLES & DENTS

In case of dents and holes use **LISBON WALL CARE PUTTY** or white cement and fine sand in the ratio 1:3. **LISBON ACRYLIC BOND DISTEMPER** should not be applied on surfaces / substrates that are subjected to continuous seepage or dampness & porosity.

TECHNICAL DETAILS

Drying time: Surface dry time 30 - 40 min

Flash point IS101/1987 Part 1,

Sec 6: Non- lammable

Stability of thinned paint: To be used within 24 hours.

PRECAUTIONS

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- Do not over-thin or over-extend the brush.
- Tint using Paints machine colourants only.
- Stir well and strain before use.
- Tinted paints need thorough shaking immediately after tinter addition as well as before use..

SAFETY FEATURES

Kindly refer to the MSDS for **LISBON ACRYLIC BOND DISTEMPER** which gives detailed information on safety measures while handling the paint, which is available on request.

Store the container with the lid tightly closed in an upright position, in a cool, dry place. Keep out of reach of children and away from eatables.

May be harmful if swallowed. In case of ingestion seek immediate medical attention.

Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

LISBON ACRYLIC BOND DISTEMPER



In Case Of Skin Contact Immediately Wash Skin With Soap And Plenty Of Water. Get Medical Attention If Irritation Develops Or Persists.

Do Not Breathe Vapour Or Spray. It Is Recommended To Wear Suitable Nose Pad During Sanding And Surface Preparation To Avoid Dust Inhalation.

Do Not Pour Leftover Paint Down The Drain Or In Water Courses.

In The Event Of Spills, Contain Spillage Using Sand Or Earth.

No Added Lead, Mercury Or Chromium Compounds.