

LISBON SATIN GLOSS

Low VOC Interior & Exterior Primum Emulsion

LISBON
CONSTRUCTION CHEMICALS & COATINGS

DESCRIPTION

Lisbon Satin Gloss Low VOC Primum Emulsion Is A Water-based Interior & Exterior Paint With Elastomeric Silicon Additives Suitable For Primum Long Lasting Finish in Dry To Moderately Humid Climatic Conditions.

PRODUCT BENEFILTS

Better Performance

Lisbon Satin Gloss Low VOC Emulsion Offers Excellent Resistance To Chalking, Cracking And Weathering In Comparison To Cement Paint. Its Modified Elastomeric Binder Ensures That Paint. Stays On Your Wall Longer Than Cement Paint.

SAVE MONEY IN THE LONG RUN

Lisbon Satin Gloss Emulsion Lasts Longer Than Cement Paint And Hence Proves More Economical In The Long Run. It Also Does Not Require Curing And Therefore Saves Time, Effort And Money During Application.

CLEAN SHADES

Lisbon Satin Gloss Emulsion Gives Neat And Clean Glossy Shades That Do Not Fade And Last Longer Than Cement Paint . It Is Available In Strong/dark Shades That Provide Excellent Hiding.

BETTER ANTI-ALGAL PERFORMANCE

Lisbon Satin Gloss Emulsion Provides Better Anti-Algai Protection Than Cement Paint Especially In Dry To Moderately Humid Climatic Conditions.

TECHNICAL INFORMATION

Surface Drying Time : 30 Mnts
Sheen Level : 3-12 at 60 degh GH
Stability Of Thinned Paint : To be used within 24 hour

CLEANING

Surface Should Be Free From Any Loose Paint, Dust Or Grease. Growths Of Fungus, Algae Or Moss Should Be Removed By Wire Brushing And Water.

COVERAGE

2 Coats 100 -120 Sqft / Ltrs.

Actual Coverage may vary from the quoted coverage due to factor such as method & condition of application & surface roughness

PACKING

Available in 1 Ltr, 4 Ltr, 10 Ltr & 20 Ltr.

PRECAUTION

Do Not Apply When Ambient Temperature Is Less Than 10°C Or If The Temperature Might Drop To This Level Within 4 Hrs Of Application. Do Not Over-thin Or Over-extend The Brush. Tint Using Paints Machine Only Stir Well And Strain Before Use. Tinted Paints Need Thorough Shaking Immediately After Tinter Addition As Well As Before Use.

STORAGE AND SHELF LIFE – Lisbon Emulsion

Must Be Stored In Unopened Packaging, Clear Of The Ground In Cool Dry Conditions And Be Protected From Excessive Draught. If Stored Correctly, As Detailed Above, The Shelf Life Of This Product Is 24 Months From The Date Shown On The Packaging.

PRECAUTIONS -

Keep Out Of Reach Of Children, Wear Suitable Protective Clothing. Gloves And Eyes/face Protection. After Contact With Skin, Wash Immediately With Plenty Of Clean Water. In Case Of Contact With Eyes Rinse Immediately With Plenty Of Clean Water And Seek Medical Advice.

DISPOSAL/SPILLAGE -

Spillage Of Any Of The Component Products Should Be Absorbed Onto Sand Or Other Inert Materials And Transferred To A Suitable Disposable Vessel. Disposal Of Such Spillage Or Empty Packaging Should Be In Accordance With Local Waste Disposal Authority Regulations.