LISBON TILE GROUT

LISBON
CONSTRUCTION CHEMICALS & COATINGS

DESCRIPTION

Lisbon Tile Grout Cementitious Grout Is A High Quality, Water Resistance, Highly Polymer Modified; Fine Cementitious Grout Designed For Grouting Ceramic, Semi And Fully Vitrified Glazed Tiles And Natural Stones. For Improved Performance, It Is Recommended To Use With Lisbon Ta/g.

FUTURE AND BENEFITS

- Easy To Use And Maintenance.
- Water And Weather Resistance.
- Non-shrinking & Non Cracking.
- Good Workability, Additional Adjustment Time.
- Self-curing.
- High Flexibility When Used With Lisbon Ta/g.

USES:

- Suitable For Grouting All Types Of Tiles And Stones.
- For Joints From 1 Mm To 7 Mm.

APPLICATION

Dampen Tile Surface With Water. Spread With A Sharp, Firm Rubber Grout Float. Work The Grout Paste Into The Joints Until Completely Filled. Use Diagonal Strokes To Pack The Joints. Ensure That Joint Is Filled And Grout Is Not Just Sitting On Top (i.e. "bridging The Joint"). Remove Excess Grout By Holding Grout Float At 70° To 90° Angle And Pulling The Float Diagonally Across The Grout Joints. Removing As Much Material As Possible Will Make Final Cleaning Easier. Allow Joint To Set For Approximately 120-180 Minutes Or Until They Begin To Firm. Time Will Vary Depending Upon Substrate And Ambient Temperature.

CURING:

Curing Time Is Affected By Ambient, Surface Temperatures And Humidity.

PACK SIZE:

AVAILABLE IN 1 KG POUCHES.

AVAILABLE COLOUR:

Available In White & Ivory Colours.

SHELF LIFE:

24 Months, If Stored In Cool And Dry Area In Unopened Containers, Protected From Sun Light. Shelf Life Is Calculated From The Month Of Manufacturing Of The Product.

CAUTION:

Protect Grouted Are From Contamination Until It Is Fully Cured. Avoid Contact With Eyes Or Skin. In Case Of Contact, Clean With Plenty Of Water And Seek Medical Attention. Use Personal Protective Instruments Such As Gloves, Goggles, Aprons, Masks, Etc While Handling The Product And Application Of Same.

LISBON TILE GROUT

COVERAGE CHART			
Approximate Lisbon Tile Grout Coverage chart (in sq.ft for 1 kg pouch)			
Tile size	1mm	2mm	A3mm
100 X 100 X 3	145	72	50
150 X 150 X 4	162	80	55
200 X 150 X 5	150	75	50
200 X 200 X 5	170	85	60
200 X 300 X 6	170	85	60
300 X 300 X 6	215	110	70
400 X 400 X 6	285	145	100
450 X 450 X 7	275	140	90
500 X 500 X 8	270	135	90
600 x 600 x 8	325	160	110