

LISBON ULTRA GRIP – 200

White & Grey



DESCRIPTION

Premium Grade Tile Adhesive Formulated For Installation Of Small To Medium Format Tile On Various Substrates. It Offers High Bond Strength And Excellent Handling Property For A Wide Variety Of Floor And Wall Tile Application.

ADVANTAGES

- Premium Grade, Strong Bonding
- Superior Quality, Easy To Fix
- Suitable For Both Floor And Wall
- Good Workability, Additional Adjustment Time
- High Performance, Low Shrinking
- Complies To National And International Standards(is 15477:2004 / EN12004 / ANSI A 118.1)

RECOMMENDED SURFACE

- Cement floors or plaster
- Cement bed
- Terrazzo

USES

- Interior Application For Floor And Wall.
- Can Fortify With Ultra Grip 200 Lisbon Admix Ta/g For Exterior Application And Improved Performance.

SURFACE PREPARATION

Surfaces Must Be Structurally Strong. Remove All Grease, Oil, Dirt, Curing Compounds, Sealers, Adhesives Or Any Other Contaminant That Would Prevent Good Bonding. Glossy Or Painted Surfaces Must Be Sanded, Or Abraded, And Stripped Off All Contaminants. Concrete Or Plaster Must Be Cured 28 Days Prior To Bonding. Concrete Must Be Free Of Efflorescence And Not Subject To Hydrostatic Pressure. Concrete Slabs Should Have A Course Finish To Enhance The Bond. Roughen The Surface By Sanding Or Abrading, Then Rinse And Allow To Dry. Expansion Joints Should Never Be Bridged With Setting Material. Surface Temperature Should Be Maintained Above 10° C Or Below 38° C To Achieve Proper Bond. For Questions About Proper Installation, Call Technical Services Executives On +91 9010616555.

TECHNICAL DATA

- Mixing Ratio: 4.5 To 5 Ltr For 20 Kg Powder
- Open Time: Approx 20 Min
- Adjustment Time: approx 20 Min
- Pot Life: Approx 4 Hrs
- Tensile Adhesion Strength (28 Days) Minimum 250 Psi (1.75 N/mm²)
- Shear Bond Strength: Minimum 300 Psi (2 N/mm²)
- Compressive Strength: Minimum 3500 Psi (24.5 N/mm²)
- Duration For Light Foot Traffic: 6 Hrs
- Duration For Normal Foot Traffic: 16 Hrs
- Duration For Heavy Foot Traffic: 24 Hrs
- Duration For Grouting: 24 Hrs

COVERAGE

50 - 60 sft / 20 kg bag for 3 mm

PACK SIZE

Available In 20 Bags In White & Grey Colour

CURING AND PROTECTION

Curing Time Is Affected By Ambient, Surface Temperatures And Humidity. Generally, Light Foot Traffic Can Be Allowed In 16 Hours At 25°c, Normal Foot Traffic In 24 Hours And Heavy Foot Traffic In 7days After Installation

SHELF LIFE

12 Months, If Stored In Cool And Dry Area In Unopened Bag.

CAUTIONS

- Store In Cool And Dry Place.
- High Humidity Or Moisture Will Affect The Product.
- Once Bag Is Opened, Then Finish It Off Without Keeping For Long Time.
- This Product Contains Portland Cement And Free Silica. Avoid Eye Contact Or Prolonged Contact With Skin.
- Wash Thoroughly After Handling. If Eye Contact Occurs, Flush With Water For 15 Minutes And Consult A Physician.
- Do Not Breathe Dust; Wear Ppe Whenever Necessary.