

LISBON WALL CARE PUTTY

LISBON
CONSTRUCTION CHEMICALS & COATINGS

DESCRIPTION

Lisbon Wall Care Putty Is A Water Resistance White Cement Based Wall Putty Ideal For Use On Concrete / Mortar Walls (internal And External) And Ceilings. It Fills The Fine Pores Of Mortar / Concrete Walls And Ceilings And Provides A White, Smooth And Dry Surface, Essential For Painting. It Has More Adhesive Strength, Durability And Enhances The Life Of Paint.

SURFACE PREPARATION

The Surface Should Be Made Clean And Free From Dust, Dirt & Other Release Agent Using Wire Brush, Sand Paper, Putty Blade And Clean Water.

Dry And Absorbent Surfaces Should Be Prewetted With Clean Water.

MIXING

Mix Lisbon Wall Care Putty (20 Kgs) With 7-8 Litres Clean Water Slowly To Make Paste. Mixing Should Be Continued Untill A Uniform Consistency Is Achieved. Mixing Could Be Done Manually Or By Suitable Electric Mixer.

APPLICATION

Apply The First Coat On Moistened Wall Surface Evenly With The Help Of Flat Trowel / Putty Blade. After Drying Of First Coat For 10-12 Hour At 25° To 30°c, Rub The Surface Gently With The Wet Sponge /putty Blade In Order To Remove The Loose Particles. Allow The Surface To Dry For Further 10-12 Hours Before Applying The Second Coat Of

Lisbon Wall Care Putty. After Drying Of Second Coat Remove Marks If Any With The Help Of Putty Blade By Gentle Rubbing. Finished Surface Shall Be Allowed To Dry Completely. Always Mix The Quantity Which Can Be Used With In 2-3 Hours. A Total Thickness Of The 2 Coats Should Be Maximum Of 2.5mm.

It Is Not Essential To Rub The Surface Done With **Lisbon Wall Care Putty**, However If You Need To Remove Unevenness Before Applying Any Kind Of Paint / Coatings, Gently Level The Walls/ceiling Surface With Very Fine Water Proof Emery Paper Of Not Less Than 500 Number To Get A Glossy White Surface.

If Required Primer Can Be Applied On **Lisbon Wall Care Putty** Before Application Of Coatings

PERFORMANCE PROPERTIES

Performance Properties:

Mixed with water:

Test

Compressive strength	>8.5 MPa
Flexural Strength	2.1 MPa
Tensile Adhesion strength	>1.0 MPa

WORKING PROPERTIES

Mixed With Water	(68°f (20°c))
Pot Life	85-100 Mins.
Initial/final Setting Time	280/300 Mins.
Water Retentivity	97% (+/-2%)
Ph	9.0-10.2

COVERAGE

12.5 Sft / Kg / Coat / (500 Sft / 40 Kg's Bag) - The Coverage Will Be Depending On The Surface Condition.

STORAGE AND SHELF LIFE

Lisbon Wall Care Putty Must Be Stored In Unopened Packaging Clear Of The Ground In Cool Dry Conditions And Be Protected From Excessive Draught.

If Stored Correctly, As Detailed Above, The Shelf Life Of This Product Is 12 Months From The Date Shown On The Packaging.

PRECAUTIONS

Keep Out Of Reach Of Children, Wear Suitable Protective Clothing.

Gloves And Eyes/face Protection.

After Contact With Skin, Wash Immediately With Plenty Of Clean Water. In Case Of Contact With Eyes Rinse Immediately With Plenty Of Clean Water And Seek Medical Advice.

DISPOSAL/SPILLAGE

Spillage Of Any Of The Component Products Should Be Absorbed Onto Sand Or Other Inert Materials And Transferred To A Suitable Disposable Vessel. Disposal Of Such Spillage Or Empty Packaging Should Be In Accordance With Local Waste Disposal Authority Regulations.